

# ZEPHYR SERIES



A symphony of quality innovations unfolds with micro vents, lift & sliding, turn & tilt systems and more, each a vital note in a harmonious collection.

**ALDABRA**

# ZEPHYR SERIES

## TECHNICAL PARAMETER

	Micro-Vent	Turn & Tilt	Lift & Slide	Folding	Skylight
<b>Profile Thickness</b>	2.0mm				
<b>Minimum Wall Width</b>	78mm	105mm	102mm	93mm	/
<b>R-Value</b>	≥4.0				
<b>Intruder Proof</b>	•	•	•	•	•
<b>Stainless Steel Screen</b>	•	•	Optional	/	/
<b>Glass Specification</b>	5mm + 12 Argon + 5mm LOW E + 1.14 PVB + 5mm				
<b>PVDF Powder Coating</b>	•	•	•	•	•
<b>Vertical Drainage</b>	•	•	•	•	•
<b>Multipoint Lock</b>	•	•	•	•	•
<b>Insulation Sealant</b>	EPDM (M - Class Rubber)				
<b>Thermal Break Profile</b>	PA66GF25 (Nylon & Fiberglass)				
<b>Wind Resistance</b>	Level 9				
<b>Water Tightness</b>	Level 6				
<b>Air Tightness</b>	Level 8				
<b>Sound Reduction</b>	≥38dB				
<b>Hardware Brand</b>	STORO	WEHAG	SOBINCO	STORO	HOPPE

# ZEPHYR SERIES

## TECHNICAL PARAMETER

2.0-2.2mm intruder-proof thermal break aluminium profile  
PVDF powder coating  
Internal vertical drainage system  
PA66FG25 Insulation Sealant  
EPDM Sealing rubber  
Double-glazed low-E & laminated high-impact glass with argon gas filling  
(5mm + 12mm Argon + 5mm Low-E + 1.14PVB + 5mm)  
Multi-point locking  
Intruder-proof ventilation

Optional feature list:

High-transparency SS security screen(SU316)  
Burglar bar  
Two-tone colors  
glass specification  
hardware and handles  
Locking options



100000  
starts




Wind resistance performance  
Level 9



Sound insulation performance  
 $\geq 35$ dB



Water tightness  
Level 6



Air tightness performance  
Level 8



Thermal insulation performance  
 $K \leq 2.4$